



**NOTE:**

- |                           |                                      |
|---------------------------|--------------------------------------|
| 1. DISPLAY TYPE:          | Yellow-Green                         |
| 2. POLARIZER TYPE:        | Reflective                           |
| 3. VIEWING DIRECTION:     | 6:00                                 |
| 4. DUTY:                  | 1/8                                  |
| 5. BIAS:                  | 1/4                                  |
| 6. LCD DRIVEING VOLTAGE:  | 4.3V(TBD)                            |
| 7. OPERATION TEMPERATURE: | 0°C-50°C                             |
| 8. STORAGE TEMPERATION:   | -10°C-60°C                           |
| 9. DRIVE IC:              | KS0066U                              |
| 10. IC PACKAGE:           | BONDING                              |
| 11. LOGIC VOLTAGE:        | 5.0V                                 |
| 12. BACKLIGHT:            | Without                              |
| 13. Cable:                | CUSTOMER PROVIDE                     |
| 13. REMARK:               | Foots of Bezel are connected to VSS. |

ALL DIMENSIONS IN MM. TOLERANCES ARE +0.3MM.

16	LED(-)
15	LED(+)
7-14	DB0-DB7
6	E
5	R/W
4	RS
3	Vo
2	Vdd
1	Vss
PIN	SIGNAL

