17815 Newhope St, Suite H, Fountain Valley, CA 92708
Tel: 714-825-0140 | Fax: 714-825-0210 | Email: sales@femacorp.com
Websites: www.fecomcorp.com | www.femacorp.com

Membrane Switch Design Sheet

1. Overlay Size (overall dimensions of part) :

2. Overlay Material : a) Polyester b) Polycarbonate
   Material Thickness :

3. Number of Colors :

4. UV Hard Coating required ?

5. Window - Size :
   Color of Window Lens :

6. Hole Cut-Outs : location and hole sizes

7. Number of Keys :

8. Flat type keys or Embossing on keys (rim emboss, dome emboss, pillow emboss)

9. Circuit Layer Switches : a) Flat key (no dome)
   b) Metal Dome (stainless steel dome)
   c) Polydome (polyester dome formed on top circuit)

10. Circuit Tail Length :
    Number of conductors on circuit tail :

11. Is a Connector assembled on circuit tail ? yes / no
    How many pins on connector : Pitch spacing on connector :
    (standard pitch is 0.10" centers)

12. Embedded LEDs on membrane switch ? : yes / no
    How many LEDs and Color :

13. ESD Shielding required ? : yes / no Specify_____

14. Rear Adhesive type: a) 3M467 adhesive
    b) 3M468 adhesive
    c) Other :

REMARKS :_____

_____

_____